

RAINFOREST COLLECTION FLOATING RECYCLED LEATHER PLANKS

ARCHITECTURAL SPECIFICATIONS

SPECIFICATIONS

Style	Floating Recycled Leather tiles a/o planks with cork backing
Description	Recycled leather mounted on a formaldehyde-free high-density fiberboard backed cork with Uniclic® interlocking joint system
Thickness	3/8"
Weight	16 oz. per square foot
Nominal Sizes	7 5/8" x 45 7/8" x 3/8"
Finish	Water-based durable floor protective finish

PERFORMANCE CHARACTERISTICS

Taber Test (ASTM d 4060 – CS 17 wheel, 500 gr)	8,000 wear through cycles
Static Load Limit (ASTM F970)	005 inch
Slip Resistance (ASTM C1028)	Dry: 0.98 Wet: 0.98
Colorfastness (AATC- 100 hrs)	Class IV
Critical Radiant Flux (C –ASTM e 648)	0.41 (Class II)
Surface Burning Characteristics (ASTM E-84)	Class C
FIIC Test (ASTM E989)	59 (no underlay) 61 (with underlay)
<i>Test conducted over 8" concrete with no suspended ceiling</i>	
Low-VOC (California standard Public School 01350)	Pass

GREEN FEATURES

Our recycled leather Floating Planks may contribute to LEED for Commercial Interiors in:

MR: 4.1/ 4.2 Recycled Content (pre-consumer)

IAC: 4.2 / 4.3 Low-emission adhesive and product

Renewable: 6.0 Rapidly renewable resource and material

EcoDomo LLC is a member of the US Green Building Council and CoopAmerica. We consider paying for carbon credits, wind-generated electricity, and recycled materials as essential as paying for rent and other utilities. Visit www.EcoDomo.com for more details.

Manufactured in the United States of America

2022 All rights reserved.